

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 October 2005 (27.10.2005)

PCT

(10) International Publication Number
WO 2005/099428 A1

(51) International Patent Classification⁷: **A01B 23/04**,
73/06, 63/24

(74) Agent: Roseann B. Caldwell; BENNETT JONES LLP,
4500 Bankers Hall East, 855 2nd Street SW, Calgary, Al-
berta T2P 4K7 (CA).

(21) International Application Number:
PCT/CA2005/000581

(22) International Filing Date: 14 April 2005 (14.04.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/521,381 14 April 2004 (14.04.2004) US

(71) Applicant (for all designated States except US):
PHOENIX ROTARY EQUIPMENT LTD. [CA/CA];
401 - 18 Avenue, Nisku, Alberta T9E 7T5 (CA).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **READ, Brian, J.**
[AU/CA]; 401 - 18 Avenue, Nisku, Alberta T9E 7T5 (CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA,
MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM,
PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: HARROW FRAME AND HARROW FORMED THEREWITH



(57) Abstract: A harrow frame may be operable to per-
mit pivoting of its ground working tool support arms be-
tween a first relative angle and a second relative angle.
Pivoting may be achieved through a drive system and
a lock controllable remotely such that the tool support
arms can be pivoted about their fulcrums "on-the-fly"
while the harrow frame is being moved along a ground
surface. In addition or alternately, a harrow frame may
also be folded to have a width less than 8.5 feet to facil-
itate transport.

WO 2005/099428 A1



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.